

Patent Pending

Made in China



Helps protect children and pets
Locks/Unlocks from both sides of door
Installs quickly to any height
Does not damage door face

DoorSmoocher™ Locks Pocket and Swing Doors

Baby Boundaries LLC
PO Box 152235
Tampa, FL 33684-2235

For Customer Support:
support@doorsmoocher.com



Enclosed: Latch Handle Assembly (1), Latch Catch (1), Spacers (3), 5/8" Screws (2), 1 1/4" Screws (2), 3/32" Drill Bit (1), Square of Two-Sided Foam Tape (2).

Tools Needed: Pencil, Drill (preferably) or Screwdriver with Phillips Head Tip.

WARNING: The DoorSmoocher™ is designed to help secure interior pocket and swing doors and under no circumstances should be considered as a replacement for adult supervision.

Keep out of reach of children under 5.

Watch a short video on how to install the DoorSmoother™ at www.doorsmoother.com

1. Center latch assembly on door at desired height (See A). Mark the two holes with pencil (See B). Latch handles should not touch door face on either side. Drill marked holes using supplied drill bit.

A



B




C



2. Place door latch handle assembly back on door with tongue of door latch facing down to floor. Screw the door latch handle to the door using the two shorter (5/8") screws supplied. Check to make sure latch handle assembly slides up and down (See C).

3. Slide latch handle into the full up position (See C). Close door and mark on the door frame the point just below the latch tongue (See D).

D



E



F




4. Take one square of the two-sided tape provided, peel one side and place it on the back of the latch catch (See E). Peel off the other side and stick the door catch on the door frame, in line with mark (See F). If the pocket door favors one side or the other when closed, stick the latch catch a little off center on the favored side.

5. Close the door to make sure the latch handle just clears the latch catch (See G). When it clears, pull the latch handle down to make sure the latch handle drops down smoothly into the closed position (See J). Adjust latch catch up or down or side to side as needed. Once the catch is placed in the right spot, mark the holes with pencil (See H).

G



H



I




J



6. Remove two sided foam from latch catch and drill two small marked holes using the supplied drill bit. Screw catch to door using longer screws (1 1/4") supplied (See I). With latch in up position, close door and slide latch handle down into door catch to insure DoorSmoother™ is dropping down fully into catch (See J).

7. If either side of the handle hits the door frame when closed (See K), a spacer(s) needs to be added to bring the door catch out in 1/8" increments until a small gap is created between the latch handle and door frame (See L), to allow the latch to slide up and down freely. If a spacer(s) is required, back the two screws out about 1/4" and drop in one spacer (See M & N) You can use a flathead screwdriver to pull catch out if it sticks. Tighten and check for clearance. Repeat process until Door Smoother™ locks smoothly from both sides.

M



N



K



L

